

## Big data: architectures and data analytics

## MapReduce Programming Paradigm and Hadoop – Part 3

Counters

2

### Counters

- Hadoop provides a set of basic, built-in, counters to store some statistics about jobs, mappers, reducers
  - E.g., number of input and output records
  - E.g., number of transmitted bytes
- Ad-hoc, user-defined, counters can be defined to compute global "statistics" associated with the goal of the application

3

### User-defined Counters

- User-defined counters
  - Are defined by means of Java enum
    - Each application can define an arbitrary number of enums
  - Are incremented in the Mappers and Reducers
  - The global/final value of each counter is available at the end of the job
    - It is stored/printed by the Driver (at the end of the execution of the job)

4

### User-defined Counters

- The name of the enum is the group name
  - Each enum as a number of "fields"
- The enum's fields are the counter name
- In mappers and/or reduces counters are incremented by using the increment() method
  - `context.getCounter(countername).increment(value);`

5

### User-defined Counters

- The `getCounters()` and `findCounter()` methods are used by the Driver to retrieve the final values of the counters

6

## User-defined Dynamic Counters

- User-defined counters can be also defined on the fly
  - By using the method `incrCounter("group name", "counter name", value)`
- Dynamic counters are useful when the set of counters is unknown at design time

7

## Example of user-defined counters

- In the driver
 

```
public static enum COUNTERS {
    ERROR_COUNT,
    MISSING_FIELDS_RECORD_COUNT
}
```
- This enum defines two counters
  - `COUNTERS.ERROR_COUNT`
  - `COUNTERS.MISSING_FIELDS_RECORD_COUNT`

8

## Example of user-defined counters

- In the mapper or the reducer
 

```
context.getCounter(COUNTERS.ERROR_COUNT).increment(1);
```
- This example increments the `COUNTERS.ERROR_COUNT` counter

9

## Example of user-defined counters

- In the driver
 

```
Counter errorCounter =
job.getCounters().findCounter(COUNTERS.ERROR_COUNT);
```
- This example retrieves the final value of the `COUNTERS.ERROR_COUNT` counter

10

## MapReduce Programming Paradigm and Hadoop – Part 3

Map-only job

11

## Map-only job

- In some applications all the work can be performed by the mapper(s)
  - E.g., record filtering applications
- Hadoop allows executing Map-only jobs
  - The reduce phase is avoided
  - Also the shuffle and sort phase is not executed
  - The output of the map job is directly stored in HDFS
    - i.e., the set of pairs emitted by the map phase is already the final output

12

## Map-only job

- Implementation of a Map-only job
  - Implement the map method
  - Set the number of reducers to 0 during the configuration of the job (in the driver)
    - `job.setNumReduceTasks(0);`

33

## MapReduce Programming Paradigm and Hadoop – Part 3

In-Mapper combiner

34

## Setup and cleanup method

- Mapper classes are characterized also by a setup and a cleanup method
  - They are empty if they are not override
- The setup method is called once for each mapper prior to the many calls to the map method
  - It can be used to set the values of in-mapper variables
  - In-mapper variables are used to maintain in-mapper statistics and preserve state within and across calls to the map method

35

## Setup and cleanup method

- The map method, invoked many times, updates the value of the in-mapper variables
- The cleanup method is called once for each mapper after the many calls to the map method
  - It can be used to emit (key,value) pairs based on the values of the in-mapper variables/statistics

36

## In-Mapper Combiners

- In-Mapper Combiners, a possible improvement over “standard” Combiners
  - Initialize a set of in-mapper variables during the instance of the Mapper
    - Initialize them in the setup method of the mapper
  - Update the in-mapper variables/statistics in the map method
    - Usually, no (key,value) pairs are emitted in the map method of an in-mapper combiner

37

## In-Mapper Combiners

- After all the input records (input (key, value) pairs) of a mapper have been analyzed by the map method, emit the output (key, value) pairs of the mapper
  - (key, value) pairs are emitted in the cleanup method of the mapper based on the values of the in-mapper variables

38

## In-Mapper Combiners

- The in-mapper variables are used to perform the work of the combiner in the mapper
  - It can allow improving the overall performance of the application
  - But pay attention to the amount of used main memory
    - Each mapper can use a limited amount of main-memory
    - Hence, in-mapper variables should be small (at least smaller than the maximum amount of memory assigned to each mapper)

19

## In-Mapper Combiner – Word count Pseudo code

```

class MAPPER
  method setup
    A ← new AssociativeArray
  method map(offset key, line l)
    for all word w in line l do
      A{w} ← A{w} + 1
  method cleanup
    for all word w in A do
      EMIT(term w, count A{w})

```

20